



MAYTAG® COMMERCIAL ON-PREMISES DRYING TUMBLER

SAVE TIME AND ENERGY COSTS

When your operation depends on a constant supply of clean laundry, the huge 170-pound capacity of the MDG170P dries more at once to maximize efficiency. Plus, the extra-large door opening makes loading and unloading easier.



MICROPROCESSOR CONTROLS

Advanced computer controls let you program drying cycles with desired drying times, temperatures and cool-down. Then select the cycle with the simple touch of a button.

FOR YOUR OPERATION:

- 170-Pound Capacity Dries More At Once
- Auto Cycle Prevents Overdrying
- Programmable Anti-Wrinkle Feature
- Display Counts Down Time Remaining In Cycle
- Extra-Large Door Opening
- Extra-Large Lint Compartment
- Easy-Access Design For Convenient Self-Service
- Optional Reverse Tumbler Feature Reduces Twisting
- Removable Top Section For Easier Installation

BUILT-TO-LAST™ FEATURES:

- Sealed Bearings Never Need Lubrication
- Heavy-Duty Motor

MDG170P




170-POUND
TUMBLER FOR
**MAXIMUM
CAPACITY.**

LAUNDRY SOLUTIONS YOU CAN *DEPEND ON.*

CLP612

On-Premises Drying Tumbler — MICROPROCESSOR CONTROL



MAYTAG® LIMITED WARRANTY

2 YEARS — ALL PARTS

For a period from the date of original purchase through the time listed above, the designated parts that fail in normal commercial use will be repaired or replaced free of charge for the part itself, with the owner paying all other costs, including labor, transportation and customs duty. Chemical damage is excluded from all warranty coverage. See complete warranty for details.



Multi-Load Dryer

DRYER SPECIFICATIONS

MODEL	MDG170P
TUMBLER	
Capacity — lbs. (kg)	170 (77.1)
Capacity — cu. ft. (cu. m)	51.2 (1.4)
Diameter — in. (cm)	51 1/2 (130.8)
Depth — in. (cm)	42 1/2 (107.9)
REVERSING TUMBLER (optional)	•
DRIVE MOTOR	
HP (kw)	7 1/2 (5.6)
AIRFLOW	
Cfm (cmm)	3,700 (104.8)
HEAT INPUT	
BTU/hr. (kcal/hr.)	550,000 (138,600)
GAS INLET	
In. (cm)	1 1/4 (3.18)
VOLTAGE/BREAKER SIZE — amps	
230V – 240V/3 PH (3-wire + ground)	60
COLOR	
White	•
APPROXIMATE WEIGHT	
Crated — lbs. (kg)	2,066 (1,009)
Uncrated — lbs. (kg)	1,900 (907)
DIMENSIONS	
A) Height — in. (cm)	100 (254)
B) Width — in. (cm)	55 1/2 (141)
C) Depth including door handle — in. (cm)	62 1/2 (158.8)
D) Floor to center of exhaust — in. (cm)	19 1/2 (49.5)
E) Exhaust diameter — in. (cm)	18 (45.7)
Door opening — in. (cm)	31 3/8 (79.7)

See specific instructions for proper installation.

Because of continuous product improvement, Maytag reserves the right to change specifications without notice.



NEW YORK CITY
M.E.A.

