



Maximum Performance



MAXIMIZE SPACE AND TIME.

UniMac's stacked washer-extractor/tumble dryer is a unique product that truly delivers increased productivity.

- Ideal for small OPL settings with limited space
- Improves throughput
- Minimal front fasteners give quick access to key washer-extractor components to improve serviceability
- Supports a higher volume than typical retail and light commercial products
- 66% more wash capacity than typical retail top load washers
- More than double production with higher capacity and faster wash times
- Reliability and durability that drastically outperforms retail or light commercial options

UNIMAC.COM

STACKED WASHER-EXTRACTOR/TUMBLE DRYERS

STACKED WASHER-EXTRACTOR/TUMBLE DRYERS

SPECIFICATIONS		UST30		UST50	
		WASHER-EXTRACTOR	TUMBLE DRYER	WASHER-EXTRACTOR	TUMBLE DRYER
Control Option		Quantum Standard		Quantum Standard	
Capacity - lb (kg)		30 (13) x 2		50 (23) x 2	
Overall Width - in (mm)		31.4 (797)		34.4 (875)	
Overall Depth - in (mm)		45.5 (1152)		51.3 (1302)	
Overall Height - in (mm)		79.7 (2023)		84.3 (2141)	
Cylinder Diameter - in (mm)		24.0 (610)	30.0 (762)	26.3 (668)	33.0 (838)
Cylinder Depth - in (mm)		16.0 (406)	26.0 (660)	20.3 (515)	30.0 (762)
Cylinder Volume - cu ft (liters)		4.2 (119)	10.6 (300)	6.3 (178)	14.8 (419)
Reversing Cylinder		-	Standard	-	Standard
Door Opening Size - in (mm)		14.3 (363)	22.6 (574)	16.3 (414)	26.9 (683)
Door Bottom to Floor - in (mm)		14.0 (356)	51.3 (1303)	14.6 (370)	52.3 (1328)
Water Inlet Connection - in (mm)		2 x 0.75 (19)	-	2 x 0.75 (19)	-
Drain Diameter - in (mm)		1 x 3 (76)	-	1 x 3 (76)	-
Drain Center Height to Floor - in (mm)		4.3 (108)	-	4.5 (115)	-
Heat Input Power - Btu/hr (kW, Mi/hr.)		-	73,000 (21.4, 77.0)	-	95,000 (27.8, 100)
Gas Connection - in		-	1/2 NPT	-	1/2 NPT
Air Outlet - in (mm)		-	8.0 (200) Elliptical	-	10.0 (250) Elliptical
Airflow - cfm (l/sec)		-	400 (190)	-	600 (285)
Motor - HP (kW)	Fan	-	0.5 (0.4)	-	0.5 (0.4)
	Drive	1 (0.75)	0.3 (0.2)	2 (1.5)	0.5 (0.4)
Total # of Speeds		6	-	6	-
Cylinder Speeds - RPM (G-Force)	Gentle	34 (0.4)	-	33 (0.4)	-
	Wash	48 (0.8)	-	46 (0.8)	-
	Distribution	86 (2.5)	-	82 (2.5)	-
	Very Low	282 (27)	-	269 (27)	-
	Low	485 (80)	-	464 (80)	-
	Medium	542 (100)	-	518 (100)	-
Electric Specs - amps	B 100-120V/50/60/1	15	15	-	-
	X 200-240V/50/60/3	15	10	15	10
	P 380-415V/50/60/3	15	10	15	10
Shipping Dimensions - in (mm)	Width	34.5 (876)		35.5 (902)	
	Depth	47.0 (1194)		54.0 (1372)	
	Height	83.0 (2108)		89.0 (2261)	
Net Weight - lb (kg)		770 (349)		910 (413)	
Shipping Weight - lb (kg)		787 (357)		930 (422)	
Agency Approvals		cUL _{us}	CSA	cUL _{us}	CSA

**TO LEARN MORE, VISIT UNIMAC.COM OR CALL 1.800.587.5458.
ALLIANCE LAUNDRY SYSTEMS - SHEPARD ST, RIPON, WI 54971**

Consult your UniMac distributor for details. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.

Authorized Distributor



Coin & Professional Equipment Company
602-248-0808
sales@cpec-laundry.com
www.cpec-laundry.com