

MULTI-LOAD WASHERS U.S./CANADA

MWS65PNATS ■ SOFT MOUNT ■ NON VEND (OPL CONTROL)



The expanded line of Maytag Commercial Washers up to a capacity of 85 pounds provides operators what they've asked for: reliable, durable equipment built to satisfy market demands.



7-IN. LCD SCREEN

This large display allows users to easily view settings, cycles, and real-time updates.



360G EXTRACTION

Shortens drying times and removes excess moisture with powerful 360G-force extraction.



CERAMIC-COATED SHAFT SLEEVE

Specially designed to help reduce friction within the drive train to support long-term durability.



REMOVABLE DISPENSER TRAYS

Simplified maintenance. Each tray can be removed without detaching the assembly.

STANDARD FEATURES

- Large door opens to 180°
- Stainless steel drum, tub, and front panel
- Multilingual controls
- USB programmable
- Choice of liquid or powder detergent in 5-compartment front soap dispenser
- Equipped for automatic soap dosing
- Large 3" drain valve



See maytagcommerciallaundry.com for warranty details.

VISIT MAYTAGCOMMERCIALLAUNDRY.COM FOR MORE INFORMATION.


®/™ © 2026 Maytag. All rights reserved.
MY250498 02/26

MULTI-LOAD WASHERS U.S./CANADA


MWS65PNATS ■ SOFT MOUNT ■ NON VEND (OPL CONTROL)




FRONT VIEW (Appearance may vary.)



SIDE VIEW



BACK VIEW



SPECIFICATIONS

MODEL	MWS65PNATS
Rated Capacity — lb (kg)	65 (29.5)
Extraction (G-Force)	360
Drum Diameter — in (mm)	27.6 (701)
Drum Depth — in (mm)	28 (719)
Drum Volume — cu ft (L)	9.8 (278)
Electrical Requirements — Volts/Hz/Phase	208-240/50-60/1
Circuit Breaker	25 A
Motor HP (kW)	5.4 (4.0)
DIMENSIONS	
Crated Width — in (mm)	40.2 (1,021)
Crated Height — in (mm)	64.5 (1,640)
Crated Depth — in (mm)	56.7 (1,440)
Drawing Dimensions	
Uncrated Width — in (mm)	A. 38.4 (975)
Drain to Door Handle — in (mm)	B. 53.5 (1,360)
Uncrated Height — in (mm)	C. 62.6 (1,590)
Uncrated Depth — in (mm)	D. 53.5 (1,359)
Door Opening to Floor — in (mm)	E. 23.7 (602)
Center of Drain to Floor — in (mm)	F. 4.3 (109)
Center of Water Connections to Floor — in (mm)	G. 54.8 (1,392)
Electrical Connection to Floor — in (mm)	H. 57.6 (1,462)
Electrical Connection to Left Side — in (mm)	I. 27.9 (709)
Cold Water Connection to Left Side — in (mm)	J. 6.4 (162)
Hot Water Connection to Left Side — in (mm)	K. 11.1 (282)
Leg Height — in (mm)	L. 1.6 (41)
Center of Drain to Side — in (mm)	M. 3.5 (88)
APPROXIMATE WEIGHT	
Uncrated — lb (kg)	1,760 (798.3)
Crated — lb (kg)	1,804 (818.3)
SPEED	
Wash RPM (G)	37 (0.53)
Spin RPM (G)	961 (360)
WATER SPECIFICATIONS	
Operating Pressure	15-87 PSI
Inlets Size — in (mm)/Connections	3/4 (19)/2
Approximate Water Consumption TOTAL — Gal (L)/cycle	49.7 (188)
Drain Valve (Outer Diameter) — in (mm)	3 (76.2)

Dimensions are for planning purposes only. See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice.

